

# ina linear guide dimensions tolerances

Our company offers different ina linear guide, ina linear technology, ina monorail guidance systems catalogue, ina linear rail catalogue at Wholesale Price? Here, you can get high quality and high efficient ina linear guide

Linear recirculating ball bearing units | Schaeffler Germany When the shoes are bolted to carriages, they form four-row linear ball bearing and guideway assemblies together with the guideways. The scrapers on the facing

INA Linear Guide Blocks KWVE Linear Bearing Guide Trolley This linear guide block is original Germany linear bearing from Schaeffler. INA linear carriage is widely used in high precision CNC machines, production lines INA Linear Rolling Bearings and Linear Plain Bearings | E.B. INA Linear Bearings are bearing elements for translation type motion. As in the case of rotary bearings, a distinction is drawn as to whether the forces occurring

@@@@@@@@								
	K	C	G	h	d	L	b	H
<a href="#">212R</a>	-	-	-	-	-	-	-	-
<a href="#">7303 BECBP</a>	-	-	-	-	-	-	-	-
<a href="#">7207 BEGBP</a>	-	-	M 24x2	-	25 mm	-	-	-
<a href="#">7310 BEGCP</a>	-	-	-	-	440 mm	-	-	-
<a href="#">7311 BEC86P</a>	-	-	-	-	110.000 mm	-	-	-
<a href="#">7311 BEC BY/W64</a>	-	-	Tr 440x5	-	440 mm	-	-	-
<a href="#">7311 BEN1GAP</a>	6	109 mm	-	-	-	-	-	-
<a href="#">7312 BEC BY/W64</a>	-	-	-	-	80 mm	-	-	-
<a href="#">7312 BEGCP</a>	-	-	-	-	-	-	-	-
<a href="#">3200 A-2ZTN9</a>	-	-	-	-	-	-	-	-
<a href="#">3200 A-2Z TN9/C3</a>	-	-	-	-	35.000 mm	-	-	-
<a href="#">3200 A-2 RS1TN9</a>	-	-	-	-	60 mm	-	-	35 mm
<a href="#">3200 A-2 RS1TN9/ C3</a>	-	85.725 mm	-	-	-	-	11 mm	-
<a href="#">5315KG</a>	-	-	Tr 950x8	-	-	-	-	-

<a href="#">5315K</a>	-	-	-	-	70.000 mm	-	-	-
<a href="#">5315WBR</a>	-	-	-	-	420.000 mm	-	-	-
<a href="#">5316WBR</a>	-	-	79.68 mm	-	80 mm	-	-	-
<a href="#">5320WBR</a>	-	-	-	-	-	-	-	-
<a href="#">5318WBR</a>	-	-	-	-	20 mm	-	-	-
<a href="#">5322WBR</a>	-	-	-	42.862 mm	-	-	-	-
<a href="#">5317WBR</a>	-	-	-	-	12 mm	-	-	-
<a href="#">5318W C1 MBR FS381</a>	-	-	-	-	-	387.35 mm	-	-
<a href="#">5319WBR</a>	-	-	-	-	12.000 mm	-	-	-
<a href="#">213R</a>	-	-	-	-	-	770 mm	-	-
<a href="#">213RDU</a>	-	-	-	-	-	419.1 mm	-	-
<a href="#">214R</a>	-	350 mm	-	-	-	-	-	-
<a href="#">214RDU</a>	-	-	-	-	240.000 mm	-	-	-
<a href="#">118KR-BKE</a>	-	-	-	-	110.000 mm	-	-	-
<a href="#">120KR-BKE</a>	-	-	-	34.925 mm	-	-	-	180.975 mm

INA Linear guides - - the Tuli shopThe RUE linear assembly consists of a TSX guide, at least one RWU carriage, and plastic plugs for the bores on the guides. All cylindrical guides and INA

INA Monorail guidance systems - TuliINA monorail guidance systems are compact linear guidance systems that are linear recirculating roller bearing and guideway assemblies RUE. ? six-row INA Linear Guide Carriage KWVE35-B-HL-G3-V1, KWVE35Four-row linear recirculating ball bearing and guideway assemblies represent the most extensive and complex group within the range of monorail guidance

INA Linear Technology - the Schaeffler GroupLinear Guidance Systems, Shafts, A. Page 5. Page 6. Linear recirculating roller bearing and guideway assemblies RUE-E are robust monorail guidance systems INA linear bearings - AHR InternationalAHR can provide the complete range of INA linear products. The INA linear range carries an expansive selction of shafting, ball bushings, guide rails and

Linear recirculating roller bearing and guideway - Albeco-D are the heavy duty designs in the range of INA linear recirculating guidance systems. It is with good reason that they are used wherever linear guidance INA Linear Guide Carriage KWSE20-G3-V1, KWSE20 - RSLinear recirculating ball bearing and guideway assemblies KUSE are full complement systems and are preloaded. They are used in applications with long